

Results of Test: Chilt/P12066

Frameless Glass Curtains Ltd

Unit 17E
Altbarn Industrial Estate
Revenge Road
Lordswood
Chatham Kent
ME5 8UD

This document confirms that performance testing was conducted from 24 July 2012 to 25 July 2012. Testing was conducted to the following standard:-

 BS 6375 Part 1:2009 Performance of windows and doors - Part 1: Classification for weathertightness and guidance on selection and specification. The following results were achieved

Product tested	Clear View Folding Sliding Doorset		
Summary of testing procedure		Result	
	Test Standard	Classification Standard	
Air permeability	BS EN 1026: 2000	BS EN 12207: 2000	600Pa (Class 3)
Watertightness	BS EN 1027: 2000	BS EN 12208: 2000	100Pa (Class 3A)
Wind resistance	BS EN 12211: 2000	BS EN 12210: 2000	1200Pa (Class C3)
Exposure category		BS 6375: Part 1: 2009	1200

Air Isakage at 50pa was 5.0m³/h positive pressure and 6.1m³/h negative pressure. The perimeter length of opening light was 8.66m.

The results relate only to the specimen tested, as detailed in the technical specification Chilt/P12066/tec1

Steve Smith - Deputy Section Head

Date: 05-04-2013

Vincent Kerrigan - Technical Manager Date:

Chiltern Dynamics

Chiltern House, Stocking Lane, Hughenden Valley, High Wycombe, HP14 4ND, United Kingdom

Tel: 01494 569800 Fax: 01494 564895

5 3.50

Web: www.chitemfire.co.uk Email: cf@chitemfire.co.uk

This document is confidential and remains the property of Chiltern International Fire Ltd.

1762 Page 1 of 6